
ISOLATION GATES

SAFELY ISOLATE DOWNSTREAM EQUIPMENT SUCH AS SCREENS AND FEEDERS DURING STOPPAGES AND MAINTENANCE.







ISOLATION GATES

Developed primarily for the needs of the iron ore industry, Transmin designs and manufactures some of the largest isolation gates in operation with opening apertures up to 12.0m long by 3.0m wide and materials up to 350mm lump size.

Most designs feature hydraulic operation using Transmin in-house designed cylinders and hydraulic power units. In addition, electric and pneumatic actuation has been supplied on the more lightly loaded duties.

Transmin also has the capability to design special gates including single or double clam shell type gates, diverter or travelling gates.

Single or Double Sliding Plates

Dependent upon the size of the aperture to be isolated, Transmin designs feature either a single-gate plate or doublegate plates, closing from each end and overlapping in the centre.

Gates over approximately 3m long will utilise double plates to optimise the cylinder size to isolate even the largest apertures.

Wear Liners

Wear liners are fitted for maximum durability and to protect the high wear edges and changes in direction of material flow.

Features

► Complete Isolation Safety

Isolation gates are primarily fitted to safely isolate downstream equipment such as Low Profile Feeders, belt feeders, screens and apron feeders, so they can be removed or worked on during maintenance campaigns.

Hydraulic Power Units

Unique hydraulic power packs with simple local control panels can be built to Transmin or client specifications.

▶ Diverse Custom Options

Transmin can customise our range of gates to suit a myriad of applications including metering, divertor or high capacity flow conditions of aggressive materials.



Diverter Gates



Local Operator Panel









Maintenance Gates

Designed as a platform to allow maintenance personnel quick and safe access for maintenance such as high wearing areas in chutes.

Hydraulic Power Units









SELECTION DATA

Please consult Transmin for confirmation of selection. Capacity range covers materials of various types of particle sizing. Non standard widths are available for special orders.

LIGHT - MEDIUM DUTY SINGLE GATES										
		600mm	800mm	1000mm	1200mm	1500mm				
GATE PLATE THICKNESS		25mm	25mm	25mm	40mm	40mm				
HPU POWER		3kW	3kW	3kW	7.5kW	7.5kW				
GATE APARTURE WIDTH	600mm	\otimes	\otimes	\otimes	\otimes	-				
	800mm	\otimes	\otimes	\otimes	\otimes	\otimes				
	1000mm	*	\otimes	\otimes	\otimes	\otimes				
	1200mm	*	*	\otimes	\otimes	\otimes				
	1600mm	*	*	*	\otimes	\otimes				
	2000mm	*	*	*	*	*				

HEAVY DUTY SINGLE GATES											
		600mm	800mm	1000mm	1200mm	1500mm	1800mm	2200mm	2600mm	3000mm	>3000mm
GATE PLATE THICKNESS		50mm	50mm	50mm	60mm	60mm	60mm	70mm	70mm	70mm	70mm
HPU POWER		7.5kW	7.5kW	7.5kW	7.5kW	18kW	18kW	22kW	22kW	22kW	22kW
GATE APARTURE WIDTH	600mm	\otimes	\otimes	\otimes	\otimes	*	*	*	*	*	*
	800mm	\otimes	\otimes	\otimes	\otimes	\otimes	*	*	*	*	*
	1000mm	*	\otimes	\otimes	\otimes	\otimes	\otimes	*	*	*	*
	1200mm	*	*	\otimes	\otimes	\otimes	\otimes	\otimes	*	*	*
	1600mm	*	*	*	\otimes	\otimes	\otimes	\otimes	\otimes	*	*
	2000mm	*	*	*	*	\otimes	\otimes	\otimes	\otimes	\otimes	*
	2400mm	*	*	*	*	*	\otimes	\otimes	\otimes	\otimes	*
	2800mm	*	*	*	*	*	*	\otimes	\otimes	\otimes	\otimes
	>2800mm	*	*	*	*	*	*	*	*	*	\otimes

HEAVY DUTY DOUBLE GATES											
		<3000mm	3000mm	3500mm	4000mm	4500mm	5000mm	6000mm	7000mm	8000mm	>8000mm
GATE PLATE THICKNESS		70mm	70mm	70mm	70mm	100mm	100mm	100mm	100mm	100mm	120mm
HPU POWER		45kW	30kW	30kW	30kW	55kW	55kW	75kW	75kW	75kW	90kW
GATE APARTURE WIDTH	<1500mm	\otimes	*	*	*	*	*	*	*	*	*
	1500mm	*	\otimes	\otimes	\otimes	\otimes	\otimes	*	*	*	*
	1800mm	*	*	\otimes	\otimes	\otimes	\otimes	\otimes	*	*	*
	2000mm	*	*	*	\otimes	\otimes	\otimes	\otimes	\otimes	*	*
	2400mm	*	*	*	*	\otimes	\otimes	\otimes	\otimes	8	*
	2600mm	*	*	*	*	*	\otimes	\otimes	\otimes	8	*
	3000mm	*	*	*	*	*	*	\otimes	\otimes	\otimes	\otimes
	>3000mm	*	*	*	*	*	*	*	*	*	\otimes



APPLICATIONS

Primary applications include stockpile outlets, dump hoppers and screen feeding bins.





HEAD OFFICE

Western Australia

Local Call: 1300 127 091

International Call: +61 (0) 8 9270 8555

Email: wasales@transmin.com.au

Address: 33-37 Denninup Way Malaga

Perth, Western Australia, 6090

Queensland & Northern Territory

Local Call: 1300 800 609

International Call: +61 (0) 7 3736 3340

Email: qldsales@transmin.com.au

INTERNATIONAL OFFICES

South America

Email: sales.sa@transmin.com.au

Brazil

Email: sales.br@transmin.com.au

North America

Email: sales.ca@transmin.com.au

www.transmin.com.au























