

HYDRATED LIME QUESTIONNAIRE

Name:	Phone:	Email:	
Company:	Site:	Project:	
Material details			
Type of Hydrated Lime and supplier?			
Particle size range?		Loose bulk density?	
How delivered to site?			
If bulk bags, what size?			
Plant requirements			
Is a storage silo(s) required? ☐ Yes	□ No	If yes what capacity?	
Is a mix tank(s) required? ☐ Yes ☐	No	If yes what capacity?	
Required solution strength?			
Required feed rate of dry lime to mix tar	nk?		
Is a transfer pump(s) to be included?] Yes □ No	If so what is solution transfer rate?	
Is a separate storage tank required?] Yes □ No	If yes what capacity?	
Is a transfer pump(s) to the process to b	pe included? ☐ Yes ☐ No	If so what is solution transfer rate?	
Transmin to include interconnecting pipi	ng?		
Transmin to include instrumentation?	□ Yes □ No		
General			
Describe any special requirements?			
Any special materials or finishes required?			
Describe the battery limits?			
Does the design need to comply with any client specific standards or specifications? ☐ Yes ☐ No			
Comments			

Please attach a sketch of the working area if available.

HEAD OFFICE

Western Australia Local Call: 1300 127 091

International Call: +61 (0) 8 9270 8555 International Fax: +61 (0) 8 9249 6116

Email: wasales@transmin.com.au

Address: 33-37 Denninup Way Malaga
Perth, Western Australia, 6090

Queensland & Northern Territory

Local Call: 1300 800 609

International Call: +61 (0) 8 9270 8555 International Fax: +61 (0) 7 3636 7355 Email: qldsales@transmin.com.au INTERNATIONAL OFFICES

South America Email: sales.sa@transmin.com.au North America Email: sales.ca@transmin.com.au

India Email: sales.in@transmin.in

www.transmin.com.au



QUICKLIME QUESTIONNAIRE

Name:	Phone:	Email:	
Company:	Site:	Project field:	
Material details			
Type of Quicklime and supplier?			
Particle size range?		Loose bulk density?	
How delivered to site?			
If bulk bags, what size?			
Plant requirements			
Is a storage silo(s) required? ☐ Yes	□ No	If yes what capacity?	
Is a slaker required? ☐ Yes ☐ No	If yes what is the re	equired feed rate of dry lime to the slaker?	
If no, to what is the lime being fed and at what rate?			
What is the F80 of the dry lime as recei	ved?		
What is the Bond Work Index (BWi) of the dry lime?			
What is the required P80 in the solution? Typically: 75 Micron			
Required solution strength? Typically: 20% w/w			
Describe slaking water quality?			
Is a separate strorage tank required?	□ Yes □ No	If yes what capacity?	
Is a transfer pump(s) to the storage tan	k be included? ☐ Yes ☐ No	If so what is solution transfer rate?	
Is a dosing pump(s) to the process to b	pe included? ☐ Yes ☐ No		
Transmin to include interconnecting piping & ducting? ☐ Yes ☐ No			
Transmin to include instrumentation?	□ Yes □ No		
General			
Describe any special requirements?			
Any special materials or finishes required?			
Describe the battery limits?			
Does the design need to comply with any client specific standards or specifications? ☐ Yes ☐ No			
Comments			

HEAD OFFICE

Western Australia Local Call: 1300 127 091

International Call: +61 (0) 8 9270 8555 Email: wasales@transmin.com.au Address: 33-37 Denninup Way Malaga

:: 33-37 Denninup Way Malaga Perth, Western Australia, 6090

Please attach a sketch of the working area if available.

Queensland & Northern Territory

Local Call: 1300 800 609 International Call: +61 (0) 8 9270 8555 Email: qldsales@transmin.com.au INTERNATIONAL OFFICES

South America Email: sales.sa@transmin.com.au North America Email: sales.ca@transmin.com.au

India Email: sales.in@transmin.in